

材質:STKM13C材

内径(Φ)	外径(Φ)	重量(m/kg)
20	26	1.70
	30	3.08
	35	5.10
25	35	3.70
	40	6.02
30	40	4.32
	45	6.94
32	40	3.55
	45	6.17
35	45	4.93
	50	9.86
40	45	2.62
	48	4.34
	50	5.55
	55	8.79
	60	12.3
45	55	6.17
	60	9.71
	65	13.6

内径(Φ)	外径(Φ)	重量(m/kg)
50	58	5.33
	60	6.78
	65	10.6
	70	14.8
55	62	5.05
	65	7.40
	70	11.6
60	70	8.01
	75	12.5
	80	17.3
63	71	6.61
	73	8.38
	75	10.2
	76.3	11.4
	80	15.0
	83	18.0
65	75	8.63
	76.3	9.84
	80	13.4
	82.6	16.0

内径(Φ)	外径(Φ)	重量(m/kg)
70	80	9.25
	82	11.2
	82.6	11.9
	85	14.3
	90	19.7
75	85	9.86
	90	15.3
	93	18.6
80	87	7.21
	90	10.5
	93	13.9
	95	16.2
	97	18.6
	100	22.2
	101.6	24.2
	103	25.9
85	95	11.1
	100	17.1
	101.6	19.1
90	100	11.7
	101.6	13.7
	105	18.0
	110	24.7
	120.5	39.6

※表は規格サイズとなります。

※別注にて特殊サイズも製作致します。お問い合わせください。

株式会社協栄ホーニング

TEL(0565)51-3077

FAX(0565)53-4373

e-mail;info@kyoei-honing.jp

材質:STKM13C材

内径(Φ)	外径(Φ)	重量(m/kg)
95	111	20.3
	117	28.8
100	107	8.93
	110	12.9
	114.3	18.9
	116	21.3
	120	27.1
	125	34.7
	130	42.5
105	120	20.8
	125	28.4
110	120	14.2
	125	21.7
	130	29.6
	135	37.8
	139.8	45.9
120	132	18.6
	136	25.3
	140	32.1
	145	40.8
	152.4	54.4

内径(Φ)	外径(Φ)	重量(m/kg)
125	134	14.4
	137	19.4
	140	24.5
	145	33.3
	148	38.7
	152.4	46.9
130	142	20.1
	148	30.8
	150	34.5
	152.4	39.0
140	150	17.9
	153	23.5
	160	37.0
	165	47.0
	168.3	53.8
	177.8	74.1
150	163.0	25.1
	165	29.2
	168	35.3
	175	50.1
	177.8	56.2
	185	72.3
	190	83.8

内径(Φ)	外径(Φ)	重量(m/kg)
160	170	20.3
	172	24.6
	175	31.0
	178	37.5
	180	41.9
	185	53.2
	190	64.7
	193	71.8
	200	88.8
170	195	56.3
	200	68.4
180	193	29.9
	196	37.1
	200	46.9
	210	72.1
	216.3	88.7
	219.1	96.2
200	213	33.1
	216.3	41.8
	230	79.5
	232	85.2
	241.8	114.0

※表は規格サイズとなります。

※別注にて特殊サイズも製作致します。お問い合わせください。

株式会社協栄ホーニング

TEL(0565)51-3077

FAX(0565)53-4373

e-mail;info@kyoei-honing.jp