

Material : STKM13C

Inner Diameter(Φ)	Outer Diameter(Φ)	Individual Weight(m/kg)
20	26	1.70
	30	3.08
	35	5.10
22	30	2.56
24	30	2.00
25	35	3.70
	40	6.02
26	47	9.45
30	36	2.44
	40	4.32
	45	6.94
	50	9.86
32	36	1.68
	37	2.13
	40	3.55
	45	6.17
35	45	4.93
	50	9.86
40	44	2.07
	45	2.62
	46	3.18
	48	4.34
	50	5.55
	55	8.79
	60	12.3
45	55	6.17
	60	9.71

Inner Diameter(Φ)	Outer Diameter(Φ)	Individual Weight(m/kg)
45	65	13.6
50	55	3.24
	56	3.92
	58	5.33
	60	6.78
	65	10.6
	70	14.8
55	62	5.05
	65	7.40
	70	11.6
56	76.3	16.6
60	65	3.85
	70	8.01
	75	12.5
	80	17.3
	85	22.3
63	68	4.04
	69	4.88
	70	5.74
	71	6.61
	73	8.38
	75	10.2
	76.3	11.4
	80	15.0
	83	18.0
65	75	8.63
	76.3	9.84

Inner Diameter(Φ)	Outer Diameter(Φ)	Individual Weight(m/kg)
65	80	13.4
	82.6	16.0
70	78	7.30
	80	9.25
	82	11.2
	82.6	11.9
	85	14.3
	90	19.7
	96.5	27.2
75	85	9.86
	90	15.3
	93	18.6
	101.6	29.0
80	87	7.21
	89	9.38
	90	10.5
	93	13.9
	95	16.2
	97	18.6
	100	22.2
	101.6	24.2
	103	25.9
85	95	11.1
	100	17.1
	101.6	19.1
90	100	11.7
	101.6	13.7

Kyoei Honing Corporation  
 Tel. +81-3-5577-3280  
 Fax. +81-3-5577-3281  
 e-mail: global-info@kyoei-honing.jp

Material : STKM13C

Inner Diameter(Φ)	Outer Diameter(Φ)	Individual Weight(m/kg)
90	105	18.0
	110	24.7
	120.5	39.6
95	111	20.3
	117	28.8
100	107	8.93
	109	11.6
	110	12.9
	114.3	18.9
	116	21.3
	120	27.1
100	125	34.7
	130	42.5
105	120	20.8
	125	28.4
	127	31.5
	130	36.2
110	120	14.2
	125	21.7
	130	29.6
	135	37.8
	139.8	45.9
120	132	18.6
	136	25.3
	140	32.1
	142	35.5
	145	40.8

Inner Diameter(Φ)	Outer Diameter(Φ)	Individual Weight(m/kg)
120	152.4	54.4
125	134	14.4
	137	19.4
	140	24.5
	142	28.0
	145	33.3
	148	38.7
125	152.4	46.9
130	142	20.1
	148	30.8
	150	34.5
	152.4	39.0
140	150	17.9
	153	23.5
	159	35.0
	160	37.0
	165	47.0
	168.3	53.8
	177.8	74.1
150	160	19.1
	163	25.1
	165	29.2
	168	35.3
	175	50.1
	177.8	56.2
	185	72.3
	190	83.8

Inner Diameter(Φ)	Outer Diameter(Φ)	Individual Weight(m/kg)
160	170	20.3
	172	24.6
	175	31.0
	178	37.5
	180	41.9
	181	44.1
	185	53.2
	190	64.7
	193	71.8
	200	88.8
170	185	32.8
	195	56.3
	200	68.4
180	193	29.9
	196	37.1
	200	46.9
	210	72.1
	216.3	88.7
	219.1	96.2
200	213	33.1
	216.3	41.8
	230	79.5
	232	85.2
	241.8	114.0
250	267.4	55.5
300	318.5	70.7

Kyoei Honing Corporation  
 Tel. +81-3-5577-3280  
 Fax. +81-3-5577-3281  
 e-mail: global-info@kyoei-honing.jp