

**Material : S45C**

Outer Diameter(Φ)	Length(ℓ)	Weight(m/kg)
5	2,000	0.15
6	2,000	0.22
8	3,000	0.39
10	3,000	0.61
12	3,000	0.89
14	3,000	1.21
15	3,000	1.39
16	3,200	1.58
18	3,200	2.00
20	3,200	2.46
22	3,000	2.99
22.4	3,000	3.07
25	3,200	3.85
28	3,100	4.83
30	3,200	5.55
31.5	3,000	6.20
32	3,000	6.32

Outer Diameter(Φ)	Length(ℓ)	Weight(m/kg)
35	3,200	7.55
35.5	3,000	7.79
40	3,350	9.87
45	3,300	12.5
50	3,200	15.4
55	3,000	18.7
56	3,000	19.4
60	3,200	22.2
63	3,000	24.5
65	3,000	26.1
67	3,000	27.7
70	3,000	30.2
71	3,000	31.1
75	3,000	34.8
80	3,000	39.5
85	3,000	44.6
90	3,000	50.0
100	3,000	61.8

\*note: the end of shaft(within 45mm) would be unapplied plating and out-of-tolerance condition.

Kyoei Honing Corporation  
Tel. +81-3-5577-3280  
Fax. +81-3-5577-3281  
e-mail : global-info@kyoei-honing.jp